# WebOPAC Installation Overview (under IIS7+)

Note that although the following uses Windows 7, the configuration is similar with Windows 2008. This document assumes some familiarity with the configuration of applications within Internet information Server (IIS) and that you have administrative permissions.

A key difference from previous versions of IIS is that the later versions of Windows/IIS have everything switched off by default, so these features need to be enabled to run WebOPAC:

### Install/Enable IIS

The following features are required as a minimum: ASP, Static content, basic authentication/windows authentication. Start > Control Panel > Programs and Features > Turn Windows features on or off (from left side navigation) to view the Windows Features dialog box

Note that different configurations may have different options selected once you open the Internet Information Services folder.



Please note that if running on a 64-bit server, you need to enable 32-bit applications in the App Pool in IIS.

	Ann line	• • • • • • • • • • • • • • • • • • •	9	al de la companya de	Actions
5	Applica	Advanced Settings	<u>· · ×</u>	4	Add Application Pool
		🗆 (General)	_	L .	Set Application Pool Defaults
ERAU\server	This page lets you vie processes, contain or	.NET Framework Version	v2.0	h worker	
on Pools	processes, contain of	Enable 32-Bit Applications	True		Application Pool Tasks
	Filter:	Managed Pipeline Mode	Integrated		Start
iult Web Site	Name 🔺	Name	DefaultAppPool		Stop
aspnet_client	Classic .NET App	Queue Length	1000	<u> </u>	💈 Recycle
		Start Automatically	True		Edit Analization Deal
images		🗆 CPU			Edit Application Pool
Support		Limit	0		Basic Settings
		Limit Action	NoAction		Recycling
WebOPA		Limit Interval (minutes)	5		Advanced Settings
		Processor Affinity Enabled	False		Rename
		Processor Affinity Mask	4294967295		
		Process Model			Kemove Remove
		Identity	pei u\webopac		View Applications
		Idle Time-out (minutes)	20		
		Load User Profile	False		нер
		Maximum Worker Processes	1		Online Help
		Ping Enabled	True		
		Ping Maximum Response Time (see	ione 90		
		Ping Period (seconds)	30		
		Shutdown Time Limit (seconds)	90		
		Startun Time Limit (seconds)	90		
		Enable 32-Bit Applications [enable32BitAppOnWin64] If set to b system, the worker process(es) servi (Windows on Windows64) mode. Pro	rue for an application pool on a 64-bit operating ing the application pool will be in WOW64 cesses in WOW64 mode are 32-bit processes OK	8	

# **Install WebOPAC**

**Important note**: You need to run the setup and configuration tools as an administrator in order to avoid error messages. Right click on the installer to do this.

[You may need to use the "Install WebOPAC to a custom directory" under later versions of Windows or where you wish to install WebOPAC to a custom location.]

# **Configure WebOPAC**

After installation of WebOPAC, run the WebOPAC configuration tool to specify the Library data path and the default Library to use. Although a default library is not strictly required, it is useful to avoid having to login to a database first.

The configuration tool is available under Library Manager (on the start menu) or from within the WebOPAC installation directory. Once configured, settings will look similar to the following:

Automatically login to	this library database: Schoo	l Library	•
	Auto-login as this user:		
Show this number of hi	ts on each 0 (Enterin	ng <mark>0 will dis</mark> play all re	sults in one scree
Web0PAC Directory:	C:\inetpub\www.root\WebOP	AC	
MLM Data Directory:	D:\DAta\WLM_Data\		Browse
	(Normally the Data directory in	n the MLM Program d	irectory)
Stop WebServer	Start WebServer	Reset	Session Details

### Set/Check File system Permissions

The Library data should be located on the same machine as WebOPAC. Full file permissions are required for the following directories:

- WebOPAC installation directory (usually C:\inetpub\wwwroot\WebOPAC)
- MLM Data directory (and subdirectories, e.g. C:\MLM\Data).

N.B. the account with these permissions must be the same as that configured within IIS for WebOPAC. You may wish to create a custom account (e.g. WebOPAC) to do this.

#### **Configure IIS**

Configure/Add the virtual directory for WebOPAC if it does not already exist.

internet Information Services (D	S Manager		
G G + ITD4L689 +	Sites + Default Web Site + WebOF	AC +	w - 5 @ -
Ele Yern Help			
Connections	A Michonald Com		Action
🖏   - 🍓 (1041899 ()1041899-Richa	/WebOPAC Conte	nt Stow At	WebOPAC Tasks Application
Application Pools	Mana	Tree A	Soutch to Features View
Default Web Site     Site	Trages	FileFe	Exprore Edit Permissions
Stal	Support Templates	File Fo File Fo	<ul> <li>And Application</li> <li>And Vinuel Directory</li> </ul>
s Site2	WebOPAC D9Unktd	File Fo Text:Di	Manage Application
	global asa	ASA Fi	Advanced Settings

Ensure the .ASP handler has been configured, so that WebOPAC can process requests.

5 ×

(Note that this may need to be added to IIS manually).

Ble View Help				
Bie View Help Connections Thouse of the table of	AveboPAC Home   Filter   Filter   Asp   Asp   Asp   Asp   Compression   Compression   Compression   Compression   Partial Document   Pror Pages   Faled Request Tracing Rules   Handler Mappings   Handler Mappings   Logging   Nodules   Modules   Note Types   Modules   Sta Settings   Sta Settings   VRL Rewrite	* * * * * * *	Actions Solver Edit Formissions Basic Settings Vew Virtual Directories Browse Applications Browse Appl	

Under authentication settings, enable anonymous to allow all users to access WebOPAC:



Within the virtual directory/application settings, configure the account that WebOPAC will use (located within basic settings):

Site name: Default Web Site Path: /		
<u>A</u> lias:	Application pool:	
WebOPAC	Classic	Select
Example: sales <u>P</u> hysical path:		
C:\inetpub\wwwroot\WebOPAC		
Connect as 'richard'	hur ]	

Note that this is the account that requires full permissions to the WebOPAC and MLM data directories. Click test settings to verify the settings (if this button is available).

If you are running with a separate application pool, ensure that the identity/account this application pool is running with (e.g. WebOPAC) has full permissions to the WebOPAC and MLM data directories.

dvanced Settlings	Contract Street	-2 <u>-</u> 2
El (General)		
.NET Framework Version	No Managed Code	
Managed Pipeline Mode	Classic	
Name	Clausic	
Queue Length	1000	
Start Automatically	True	
🖹 CPU		
Limit	0	
Limit Action	NaAction	
Limit Interval (minutes)	5	
Processor Affinity Enabled	False	
Processor Affinity Mask	4294967295	
Process Model		
Identity	eichaed	
Idle Time-out (minutes)	20	100
Load User Profile	Faise	
Maximum Worker Processes	1	
Ping Enabled	True	
Ping Maximum Response Time (seconds)	90	
Ping Period (seconds)	30	
Shutdown Time Limit (seconds)	90	
Startup Time Limit (seconds)	90	
E Process Orphaning		
Excluded	Extra	
Identity [identityType, username, password] Configures the Identity (recommended), Network Service, Local Sy	application pool to run as built- in accoun stem, Local Service, or as a specific user id	t, ke. Application Pool entity.
		OK Cancel

Now try running WebOPAC. The default URL path is

http://localhost/webopac/ Note that if you do not have default documents specified, you may need the full URL: http://localhost/webopac/mlmweb1.asp

## Troubleshooting

Typical installation issues relate to the incorrect setting of permissions. This will appear as an error similar to the following:

	Search:	for:		
Mone	New Search	1 My Record	le Login	🛈 Help

You can resolve this by rechecking your WebOPAC and MLM data permissions.

Additionally you may receive an upgrade message when attempting to use a particular database:

	Search	fors	~	
Home	New Search	My Record	Te Login	🕕 <u>Help</u>

To resolve this issue, you need to open the database within the latest version of Library Manager.

It is possible to run WebOPAC with data located on another machine, however you will need to use a domain level account which has the required permissions on both machines.

